



Caractéristiques:

Logistique

FUTURELIGHT LED PXS-40 Artnet Strip

LED bar for video and pixel mapping applications via Art-Net

- Modular LED strip with 40 pixels for video and pixel mapping applications via Art-Net
- Data and power supply via optional video processor
- Extra bright and colorful projection of videos, animations and graphics
- Modular concept allows the build-up of large areas
- Ideal for rental companies, stage/fair construction and fixed installation
- For use with MADRIX or any other lighting control software supporting Art-Net
- RGB SMD 5050 LEDs, covered by a smooth diffuser plate, provide excellent color rendering and wide viewing angles
- Signal distribution via UTP cable
- Movable mounting bracket for flexible installation
- 40 LED SMD 5050 3in1 RGB (mélange de couleurs homogène)
- Utilisable dans le mode CH DMX 120
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via RDM; Art-Net

FUTURELIGHT PSU-16 Artnet Controller

Video processor for LED PXS-40 + PXS-20 Art-Net Strip

- Video processor and power supply unit for LED PXS-40/20 Artnet Strip

- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 16 LED PXS-40 Artnet Strips
- 2 x 16-digit LCD screen for menu settings
- Integrated web interface for comfortable configuration and firmware updates through a browser
- Useful software tool scans the network and identifies fixtures
- Neutrik PowerCon input and output
- Signal distribution via UTP cable
- Switch-mode power supply for operation between 100 and 240 volts
- Commandé via Art-Net; RDM

Données techniques:

Poids: 33,95 kg

FUTURELIGHT LED PXS-40 Artnet Strip

Puissance totale de raccordement: 18,00 W

Type de lampe: Lampe LED

Type de LED: 40 x SMD 5050 3in1 RGB (mélange de couleurs homogène)

Canaux DMX: 120

Refroidissement: Refroidissement par convection passive

Commande: RDM; Art-Net

Couleur du boîtier: Noir

Dimension: Longueur : 100 cm
Profondeur : 3,8 cm
Hauteur : 14 cm

Poids: 1,95 kg

Power supply: 28 V DC via video processor (accessory)

Protocol: Art-Net 3

Pixel configuration: RGB SMD 5050

Resolution: 40 pixels

Pixel pitch: 25 mm

Brightness: 850 cd/m² (nits)

Viewing angle: 120°

Display refresh rate: 400 Hz

Video refresh rate: 60 fps

Signal port: 2 x RJ45, CAT5e

Produit spécial: Non destiné à l'éclairage de la pièce dans les ménages

Utilisation: Éclairage pour effets de spectacle

FUTURELIGHT PSU-16 Artnet Controller

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 300,00 W

Connexion au réseau:	Protocole : Art-Net 3 via 2x RJ-45 (F) version encastrable
Commande:	Art-Net; RDM
Couleur du boîtier:	Noir
Connexions:	Signal via 4 x RJ-45 (F) version encastrable
Dimension:	Largeur : 26 cm Profondeur : 22,6 cm Hauteur : 8 cm
Poids:	2,75 kg

Contenu de la livraison:
