

## OMNITRONIC RS-802 Recording mixer

Well-structured 8-channel studio and live mixer

Réf. : 10040075

GTIN: 4026397183245



L'article n'est plus disponible.

### Caractéristiques:

- Low-noise 8-channel mic/line mixer
- 4 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux Send per channel for controlling external effectors
- Stereo Aux Return with balanced 6.3 mm jack sockets
- Separate Main Mix, Booth and headphones outputs
- Tape inputs assignable to Master, Booth/headphones
- Precise 10-fold stereo LED meter

### Logistique

EAN / GTIN: 4026397183245

Poids: 3,25 kg

Longueur: 0.37 m

Largeur: 0.31 m

Hauteur: 0.12 m

### Données techniques:

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Puissance totale de raccordement: | 15,00 W                                                   |
| Dimension:                        | Largeur : 27 cm<br>Profondeur : 25 cm<br>Hauteur : 5,5 cm |
| Poids:                            | 2,75 kg                                                   |
| Power supply:                     | 2 x 20 V AC, 50/60 Hz<br>via included power unit          |
| Inputs:                           |                                                           |

|                         |                             |
|-------------------------|-----------------------------|
| 4 x mono                | XLR or balanced 6.3 mm jack |
| 2 x stereo              | balanced 6.3 mm jacks       |
| 1 x Aux Return:         | balanced 6.3 mm jacks       |
| 1 x Tape In             | stereo RCA                  |
| Outputs:                |                             |
| 1 x Master Out          | balanced 6.3 mm jacks       |
| 1 x Control Room        | balanced 6.3 mm jacks       |
| 1 x Aux Send:           | balanced 6.3 mm jacks       |
| 1 x Tape Out            | stereo RCA                  |
| Frequency range:        |                             |
| Microphone:             | 10-60000 Hz, ±3 dB          |
| Mono:                   | 10-60000 Hz, ±3 dB          |
| Stereo:                 | 10-55000 Hz, ±3 dB          |
| Distortion:             | 0.01 %                      |
| S/N ratio:              | 112 dB                      |
| Tone control/channel:   |                             |
| Treble:                 | ±15 dB at 12 kHz            |
| Middle:                 | ±15 dB at 2.5 kHz           |
| Bass:                   | ±15 dB at 80 Hz             |
| Dimensions (W x D x H): | 270 x 250 x 55 mm           |