

# OMNITRONIC LRS-1202 Live Recording Mixer

Live recording mixer with 12 inputs

Réf. : 10040223

GTIN: 4026397449129



## Caractéristiques:

- 4 mono input channels with gain control, 3-way EQ and pan control
- 4 stereo input channels with 3-way EQ and balance control
- Adjustable stereo aux return input and FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

## Logistique

EAN / GTIN: 4026397449129

Poids: 2,20 kg

Longueur: 0.33 m

Largeur: 0.29 m

Hauteur: 0.09 m

## Données techniques:

|                                   |  |
|-----------------------------------|--|
| Alimentation électrique:          | 230 V AC, 50 Hz  |
| Puissance totale de raccordement: | 10,00 W  |
| Branchement électrique:           | Alimentation électrique via mini DIN 3 broches (M) version encastrable câble d'alimentation à prise euro (inclus dans la livraison)<br>Tramite |
| Plage de fréquence:               | 20 - 20000 Hz  |
| Dimension:                        | Largeur : 22,5 cm<br>Profondeur : 5 cm   |

|                         |                                       |
|-------------------------|---------------------------------------|
|                         | Hauteur : 24,5 cm                     |
| Poids:                  | 1,80 kg                               |
|                         | via supplied PSU                      |
| Inputs/sensitivity:     |                                       |
| Mic, mono               | 0.5 mV, combined XLR/6.3 mm jack bal. |
| Insert                  | 140 mV, 6.3 mm jack unbal.            |
| Line In, stereo         | 60 mV, 6.3 mm jack L/R bal.           |
| Aux Return:             | 60 mV, 6.3 mm jack L/R bal.           |
| Tape In                 | 400 mV, RCA L/R                       |
| Outputs/level:          |                                       |
| Main Out:               | 800 mV. 6.3 mm jack L/R unbal.        |
| Control Room            | max. 3 V, 6.3 mm jack L/R unbal.      |
| FX Send                 | max. 10 V, 6.3 mm jack unbal.         |
| Tape Out                | 60 mV, RCA L/R                        |
| Headphones              | 6.3 mm jack unbal.                    |
| Headphones impedance:   | >8 ohms                               |
| Distortion:             | <0.04 %                               |
| S/N ratio:              | 91 dB                                 |
| Tone control/channel:   |                                       |
| Treble:                 | ±15 dB at 12 kHz                      |
| Middle:                 | ±15 dB at 2.5 kHz                     |
| Bass:                   | ±15 dB at 80 Hz                       |
| Dimensions (W x D x H): | 225 x 245 x 50 mm                     |

### Contenu de la livraison: