

OMNITRONIC MRS-1202USB Recording Mixer

Compact audio mixer with 12 inputs and USB interface

Réf. : 10040272

GTIN: 4026397513899



L'article n'est plus disponible.

Caractéristiques:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- Full duplex USB port: simultaneous recording and playback possible
- 2 mono input channels with gain control, 3-way EQ, Low Cut and pan control
- 4 stereo input channels with level switch and balance control
- Adjustable stereo aux send output
- Tape input and output
- Separate main mix and control room outputs
- Headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit
- Rugged, compact metal housing

Logistique

EAN / GTIN: 4026397513899

Poids: 2,58 kg

Longueur: 0.37 m

Largeur: 0.30 m

Hauteur: 0.08 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	28,00 W
Branchement électrique:	Alimentation électrique via fiche creuse (M) version encastrable câble d'alimentation et bloc d'alimentation (inclus dans la livraison)
	Tramite
Plage de fréquence:	20 - 20000 Hz

Rapport signal/bruit:	>74 dB
Port USB:	USB 2.0, type B
Dimension:	Largeur : 35,5 cm Profondeur : 34,5 cm Hauteur : 11,5 cm
Poids:	2,35 kg
Inputs/sensitivity:	
Mic, mono	0.5 mV, XLR bal.
Line In, mono	0.5 mV, 6.3 mm jack bal.
Line In, stereo	10 mV, 6.3 mm jack L/R
Tape In	100 mV, RCA L/R
Outputs/level:	
Main Out:	650 mV, 6.3 mm jack L/R unbal.
Control Room	2 V max. 6.3 mm jack L/R unbal.
Aux Send:	2 V, 6.3 mm jack unbal.
Tape Out	2 V, RCA L/R
Headphones	2 V, 6.3 mm jack unbal.
Distortion:	0.05 %
Tone control/channel:	
Treble:	±15 dB at 12 kHz
Middle:	±15 dB at 2.5 kHz
Bass:	±15 dB at 80 Hz
Phantom power:	+48 V