

OMNITRONIC L-300, Amplifier 2x150W/4 ohm

Reliable PA amplifier for starters

Réf. : 10450670

GTIN: 4026397243062



L'article n'est plus disponible.

Caractéristiques:

- 2 x 150 W/4 ohms
- Enormous power with highest brilliance
- 2 gain controls on the frontpanel
- All operation modes controllable via LEDs
- Signal inputs via XLR female or 6.3 mm jack socket
- Speaker connection via lockable Speaker plugs
- Ground lift switch against humming
- Bridged switch for bridging
- Protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation

Logistique

EAN / GTIN: 4026397243062

Poids: 9,70 kg

Longueur: 0.51 m

Largeur: 0.42 m

Hauteur: 0.10 m

Données techniques:

Puissance totale de raccordement:	650,00 W
Puissance de sortie:	75 W RMS (8 Ohm)
Plage de fréquence:	10 - 50000 Hz
Dimension:	Largeur : 48,3 cm Profondeur : 35 cm Hauteur : 4,45 cm
Poids:	8,70 kg
Power supply:	115/230 AC V AC, 50/60 Hz

Power output (RMS):	
Stereo 4 ohms	2 x 150 W
Stereo 8 ohms	2 x 75 W
8 ohms bridged	1 x 300 W
Signal-to-noise ratio:	>100 dB
Total harmonic distortion:	0.05 %
Damping factor:	>150
Slew rate:	70 V/μsec.
Crosstalk:	>70 dB
Input impedance:	20 kohms
Input connectors:	2 x XLR, 2 x Jack mounting socket
Output connectors:	2 x Speaker
Protection:	Overheat, overload, short-circuit, DC, softstart
Cooling:	Temperature-controlled fan
Controls:	Power switch, input attenuators, Mode switch - Stereo/Parallel/Bridged, Ground Lift
Indicators:	Power, Clip, Protect, Parallel, Bridge
Construction:	Steel chassis, aluminum front panel
	Rack installation with 1 u