

OMNITRONIC E-300 MK2 Amplifier

Stereo PA amplifier with limiter, 2 x 150 W/4 ohms

Réf. : 10451056

GTIN: 4026397512083



Caractéristiques:

- 2 operating modes can be selected (stereo or bridged) with LED indicators
- Limiter, switchable
- Speaker switch-on delay
- 2 level controls
- Each channel with LED for activated protective circuit (protect) and 7-fold output meter with clip LED
- Complete protection set against short-circuit, overheat, DC voltage, power on/off transients
- Groundlift switch against humming
- Fan cooling
- Signal inputs via XLR or RCA jacks, with XLR feed-through output
- Speaker outputs via lockable Speaker jacks and pairs of screw terminals
- Additional Speaker plug for 8-ohm bridge operation
- Rack installation with 2 units
- (19") 48,3 cm installation en rack

Logistique

EAN / GTIN: 4026397512083

Poids: 7,85 kg

Longueur: 0.51 m

Largeur: 0.37 m

Hauteur: 0.15 m

Données techniques:

| | |
|-----------------------------------|------------------------------------|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 1891,00 W |
| Puissance de sortie: | 100 W RMS (8 Ohm) |
| Commutation: | Class AB |
| Conception du boîtier: | (19") 48,3 cm installation en rack |

| | |
|----------------------|--|
| Dimension: | Largeur : 48,3 cm Profondeur : 34,5 cm Hauteur : 8,9 cm |
| Poids: | 6,95 kg |
| Power output sine: | |
| Stereo 4 ohms | 2 x 150 W |
| 8 ohms bridged | 1 x 300 W |
| Frequency range: | 10-50000 Hz, ± 1.5 dB |
| Damping factor: | >350 |
| Distortion factor: | 0.1 % |
| Slew rate: | 40 V/ μ sec |
| S/N ratio: | >90 dB |
| Channel separation: | >70 dB/ 1 kHz |
| Input sensitivity: | 0.77 V |
| Input impedance: | 20 kohms |
| Input voltage: | max. 21 dBV/9V |
| Input connectors: | 2 x XLR, 1 x stereo RCA |
| Output connectors: | 2 x Speaker, 1 x Speaker (bridge), 2 x pairs of screw terminals, 2 x XLR (feed-through output) |
| Control elements: | power switch, level control per channel, mode switch (stereo/bridged), limiter selector, groundlift selector |
| LED indicators: | stereo, bridged (globally), protect, and 7-fold output meter with clip LED (per channel) |
| Protection circuits: | short-circuit, overheat, DC voltage, power on/off transients, softstart |
| Construction: | steel chassis with aluminum front panel |
| Dimensions (DxWxH): | 345 x 482 x 100 mm (19", 2 U) |

Contenu de la livraison: