

## OMNITRONIC PSM-6.5A Studio monitors/pair

Moniteur actif 2 voies pour champ proche

Réf. : 11036473

GTIN: 4026397192667



### Caractéristiques:

- Balanced frequency range for uncolored playback
- For studio use, home recording or high-end playback in living rooms
- Magnetic shielding for use next to computer monitors etc.
- Ferrofluid-cooled tweeter for brilliant treble
- Two independent amplifiers for HF and LF
- Active 2-way crossover
- Bass-reflex system
- Gain control for adjusting the input signal
- Dip switches for adjusting the monitor to the environmental conditions
- Limiter, switchable for avoiding clipping
- Line signal connection via XLR/jack socket
- Rugged MDF wood housing
- Packed as a pair (2 pieces)

### Logistique

EAN / GTIN: 4026397192667

Poids: 26,50 kg

Longueur: 0.62 m

Largeur: 0.04 m

Hauteur: 0.52 m

### Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

Puissance totale de raccordement: 115,00 W

Puissance de sortie: Max. 85 W

Plage de fréquence: 40 - 20000 Hz

Dimension: Largeur : 41,5 cm  
Profondeur : 24,5 cm

	Hauteur : 28,5 cm
Poids:	24,50 kg
Amplifier power:	
HF:	30 W
LF:	85 W
Components:	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")
Connection:	XLR/jack socket
Sensitivity:	90 dB
Crossover:	2.5 kHz
Total Harmonic Distortion:	0.05 %
Min. input sensitivity:	1 V
Input impedance:	10 kohms
Gain control:	-6/+9 dB
HF/MF-adjustment:	±2 dB @ 10-20 kHz
LF-adjustment:	±2 dB @ 20-80 Hz
Dimensions (H x W x D):	415 x 245 x 285 mm

### **Contenu de la livraison:**