

OMNITRONIC PSS-12A Studio subwoofer

The completion for your studio monitors

Réf. : 11036476

GTIN: 4026397207699



L'article n'est plus disponible.

Caractéristiques:

- Can be used for PSM-6.5, PSM-6.5A and all other passive systems in need of bass support
- High efficiency
- Signal input via RCA, XLR or 6.3 mm plugs
- Signal output via XLR plugs
- Level control
- Low-pass filter, continuously adjustable
- Phase inversion switch
- Footswitch to switch subwoofer on/off
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Logistique

EAN / GTIN: 4026397207699

Poids: 31,50 kg

Longueur: 0.73 m

Largeur: 0.55 m

Hauteur: 0.48 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	250,00 W
Puissance de sortie:	Max. 150 W
Plage de fréquence:	50 - 150 Hz
Dimension:	Largeur : 45 cm Profondeur : 38 cm Hauteur : 54 cm
Poids:	27,00 kg

Amplifier power:	150 W
Components:	12" long excursion woofer
Inputs:	XLR/jack combination, RCA
Outputs:	XLR
Footswitch:	6.3 mm jack
Sensitivity:	90 dB
HP filter:	adjustable down to 60 Hz
THD:	0.05 %
Min. input sensitivity:	1 V
Input impedance:	10 kohms
Dimensions (H x W x D):	450 x 380 x 540 mm