



L'article n'est plus disponible.

Caractéristiques:

- Dedicated PA speaker system for fixed installations
- 2-way speaker system with 16.5 cm polypropylene woofer (6,5") and 2 cm dome tweeter (0.75") with horn front attachment
- Highly efficient bass-reflex system
- Well-balanced and clear sound, capable of high volumes
- 2-way tone control and level control
- Signal input and output via XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Delivery includes movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.

Logistique

EAN / GTIN: 4026397272239

Poids: 11,60 kg

Longueur: 0.51 m

Largeur: 0.23 m

Hauteur: 0.37 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	80,00 W
Plage de fréquence:	55 - 20000 Hz
Dimension:	Largeur : 20,8 cm Profondeur : 20,3 cm Hauteur : 34,8 cm
Poids:	10,79 kg
Program power:	50 W

Components:	16.5 cm woofer (6.5"), 2 cm horn (0.75")
Connection:	3-pin XLR
Maximum SPL:	103 dB
Impedance:	8 ohms
Dimensions (H x W x D):	348 x 208 x 203 mm