

## OMNITRONIC AS-1500 MKII Active system

Powerful compact active PA system, 1500 watts

Réf. : 11038822

GTIN: 4026397404463



**L'article n'est plus disponible.**

### Caractéristiques:

- Mobile subwoofer/satellite system with integrated 3-channel amplifier, 2-way crossover and limiter
- Very high durability and high SPL - ideal for solo entertainers, bands and mobile DJs
- Several AS-1500 systems can be used to set up large PA systems
- Integrated SMPS
- 45 cm subwoofer in bass-reflex cabinet provides powerful, dry bass
- Tops with 25 cm bass-midrange speakers and 2 cm constant directivity horn with coil-driver and passive 2-way crossover
- Balanced inputs via combo jacks (XLR/6.3 mm) and parallel outputs (XLR) for feed-through of the input signal to a second system
- Satellite speaker connection via lockable Speaker plugs
- Complete protection set, among others with opto limiter and subsonic filter against extremely low frequencies
- Level controls for the subwoofer and the satellite speakers, as well as bass and treble EQ for the the satellite speakers
- Subwoofer in multiplex wood cabinet, satellite speakers in MDF cabinet with scratch-resistant lacquer surface and impact-resistant steel grille with acoustic foam
- Satellite speakers with stand flanges and trapezoidal shape for easy clustering
- Subwoofer also with D20 thread for accepting a speaker stand tube and two swivel castors and two fixed castors for easy transportation
- Tops can be used lying, standing, suspended, mounted to a stand or to a stand tube on the subwoofer
- Subwoofer can be used lying or standing
- Delivery includes two 5-meter speaker cables from the subwoofer to the satellite speakers

### Logistique

EAN / GTIN: 4026397404463

Poids: 52,15 kg

Longueur: 0.82 m

Largeur: 0.59 m

Hauteur: 0.71 m

Article encombrant

## Données techniques:

|                                     |                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Alimentation électrique:            | 230 V AC, 50 Hz                                                                                                  |
| Puissance totale de raccordement:   | 1700,00 W                                                                                                        |
| Puissance de sortie:                | Max. 1500 W                                                                                                      |
| Plage de fréquence:                 | 120 - 18000 Hz                                                                                                   |
| Dimension:                          | Largeur : 52 cm<br>Profondeur : 70 cm<br>Hauteur : 65 cm                                                         |
| Poids:                              | 28,15 kg                                                                                                         |
| Satellite speakers:                 |                                                                                                                  |
| Rated power:                        | 300 W RMS                                                                                                        |
| Program power:                      | 450 W                                                                                                            |
| Components:                         | 25 cm woofer (10"), 2 cm horn (0.75")                                                                            |
| Connection:                         | 1 Speaker jack                                                                                                   |
| Sensitivity:                        | 99 dB                                                                                                            |
| Maximum SPL:                        | 121 dB                                                                                                           |
| Impedance:                          | 4 ohms                                                                                                           |
| Crossover frequency:                | 2.5 kHz                                                                                                          |
| Dispersion angle:                   | 60° x 90°                                                                                                        |
| Dimensions (H x W x D):             | 320 x 310 x 520 mm                                                                                               |
| Subwoofer:                          |                                                                                                                  |
| Rated power:                        | 900 W RMS                                                                                                        |
| Program power:                      | 1200 W                                                                                                           |
| Components:                         | 45 cm woofer (18")                                                                                               |
| Inputs:                             | 2 x combo jack XLR/6.3 mm                                                                                        |
| Through:                            | 2 x XLR                                                                                                          |
| Outputs:                            | 2 x Speaker                                                                                                      |
| Sensitivity:                        | 101 dB                                                                                                           |
| Maximum SPL:                        | 127 dB                                                                                                           |
| Impedance:                          | 8 ohms                                                                                                           |
| Dimensions (H x W x D):             | 650 x 520 x 700 mm                                                                                               |
| Amplifier:                          |                                                                                                                  |
| Total power output:                 | 1500 W RMS                                                                                                       |
| Power output to satellite speakers: |                                                                                                                  |
| Stereo 4 ohms:                      | 2 x 560 W (RMS)                                                                                                  |
| Stereo 8 ohms:                      | 2 x 350 W (RMS)                                                                                                  |
| Nominal power output subwoofer:     | 900 W RMS                                                                                                        |
| Min. input sensitivity:             | 0.775 V                                                                                                          |
| Control elements:                   | power switch, satellite level control, low/high equalizer, subwoofer level control, frequency crossover, limiter |
| LED indicators:                     | power and signal/limit per channel                                                                               |

|                       |                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------|
| Protection circuits:  | short-circuit, DC voltage, thermal protection,<br>softstart, opto limiter, subsonic filter |
| Equalizer:            |                                                                                            |
| Tone control/channel: |                                                                                            |
| Treble:               | ±10 dB at 10 kHz                                                                           |
| Bass:                 | ±10 dB at 75 Hz                                                                            |
| Active crossover:     |                                                                                            |
| Crossover frequency:  | 50-250 Hz                                                                                  |