

OMNITRONIC MAXX-1810 2 voies Top 2x

2 x enceintes large bande passives 10", 150 W RMS

Réf. : 11038838

GTIN: 4026397663150



Prix de catalogue: 391.51 €

TVA 19% incl.

Description:

The MAXX-1810DSP is an active 2.1 PA system with 700 watts of continuous power (1400 watts peak) and 123 dB maximum SPL capability. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 18" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 10" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1810DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1810DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

Logistique

EAN / GTIN: 4026397663150

Poids: 21,25 kg

Longueur: 0.57 m

Largeur: 0.32 m

Hauteur: 0.52 m

Caractéristiques:

- Système bass-reflex à 2 voies avec haut-parleur médium 10" et driver de compression 1"
- Forment un système 2.1 puissant avec le subwoofer MAXX-1810
- Avec filtre passif à 2 voies, y compris protection PTC pour les aigus
- Avec points de vol
- Métalgrille en noir

- Poignée de transport robuste
- Pour des domaines d'application tels que: Usage portable; DJ itinérants / artistes solos; bailleur
- Possibilité d'utilisation: Volant; monitoring; sur trépied; debout

L'étendue des fournitures

- 2 x tête d'ampli, 2 x câble d'enceinte

Données techniques:

Capacité de charge:	Programme: 300W Nominale: 2x 150W RMS
Plage de fréquence:	90 - 18000 Hz
Sensibilité:	93 dB
Pression acoustique max.:	119 dB
Dispersion:	90° x 60°
Impédance:	4 Ohm
Système d'enregistrement:	Bride: Ø 35 mm
Points d'accroche:	5 x Filetage M8
Connexions:	Entrée: Enceinte via 1 x Boîtier d'enceinte encastrable (F)
Enceinte:	1 x Boumeur 10" 1 x pilote de compression aigus 1"
Type d'enceinte:	Boîtier compact
Poignée de transport:	1 Pièce
Dimension:	Largeur : 28,5 cm Profondeur : 28,8 cm Hauteur : 46,6 cm
Poids:	19,95 kg