

OMNITRONIC ACS-510 Active System

Système de haut-parleurs actifs PA avec table de mixage à 3 canaux, 510 W

Réf. : 11038860

GTIN:



Description:

Active PA System with 3-Channel Mixer, 510 Watts

The ACS-510 is an active PA system with impressive volume reserves and superb audio performance for DJs and musicians on the go. It's super-compact, exceedingly lightweight and offers flexible setup options.

The intelligent design with a 10" subwoofer and satellite speakers allows for a 2.1 setup as well as a full-range speaker setup in mono mode. The satellites can be stacked without cables and be linked to the subwoofer cabinet by means of a smart click mechanism. Two ACS-510 can be doubled up to create a more powerful stereo system.

The integrated amplifier supplies a power of up to 510 watts and is protected with a limiter. The 3-channel mixer offers a wide range of inputs to connect your microphone, keyboard, MP3 player and laptop.

For hassle-free transport, the satellites can be stored in the back of the subwoofer cabinet. Delivery includes two speaker cables and variable stands which can also be used as distance tubes on the subwoofer:

Caractéristiques:

- Ultra-compact PA speaker system for mobile DJs and musicians
- Intelligent design enables sound characteristics of much larger PA systems
- Delivers crystal-clear sound and rich lows in various kinds of mobile PA applications
- Flexible use: mono, 2.1 or stereo setup with 2 systems linked together
- Smart click mechanism allows stacking satellites in mono mode without cables
- 1 active 25 cm bassreflex subwoofer (10") with flange
- 2 satellites with 12 cm midrange speaker (4.75") and 25 mm CD tweeter

Logistique

- 130 dB max. SPL (peak)
- 2-channel amplifier system with 1 x 350 W for subwoofer and 2 x 80 W or 1 x 160 W for satellites
- Efficient class D circuitry
- Integrated 3-channel mixer
- 1 mono input mic/line
- 1 stereo input mic/line
- 1 stereo line input
- Volume and tone control per channel
- Link connection for combining two PA systems and double output power
- Record and feed-through outputs
- Low-resonance polystyrene enclosure (HIPS) with bassreflex port
- Total weight just 18 kg
- Subwoofer with convenient transport compartment for satellites
- Set incl. 2 variable tripods (can be used as distance tubes) and 2 speaker cables for 2.1 setup

Données techniques:

Poids: 22,20 kg

OMNITRONIC ACS-510 Lautsprecheranlage

| | |
|-----------------------------------|--|
| Alimentation électrique: | 115/230 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 100 W alimentation 1/8 |
| Connexions: | Sortie: rec. via 1 x Prise 6,3 mm (asym.) Sortie: Enceinte via 2 x Prise 6,3 mm (asym.) Lien: Line via 1 x Prise jack 6,3 mm (stéréo) version encastrable |
| Entrée des canaux: | 1 x Mono avec interrupteur Mic-Line via Prise combo (XLR/jack), réglage du canal via bouton rotatif 1 x Stéréo avec interrupteur Mic-Line via Prise combo (XLR/jack), réglage du canal via bouton rotatif 1 x Stéréo via RCA ou câble jack, réglage du canal via bouton rotatif |
| Poids: | 20 kg |
| Puissance de sortie: | 2 x 80 W RMS (8 Ohm) |
| Pression acoustique max.: | 130 dB |
| Dispersion: | 90° x 10° jusqu'à -45° |
| Enceinte: | 1 x enceinte médium 4,75" 1 x pilote de compression aigus 1" |
| Dimension: | Largeur : 14,2 cm Profondeur : 10,9 cm Hauteur : 22,8 cm |
| Puissance de sortie: | 350 W RMS (4 Ohm) |
| Plage de fréquence: | 50 - 160 Hz |
| Pression acoustique max.: | 123 dB |
| Enceinte: | 1 x Boumeur 10" |
| Dimension: | Largeur : 34,5 cm Profondeur : 40,5 cm Hauteur : 46 cm |

Contenu de la livraison:

1 x basse

1 x tête d'ampli