

OMNITRONIC TMC-3 Interface incl. VDJ

MIDI controller and audio interface incl. software Virtual DJ LE

Réf. : 11045044

GTIN: 4026397418729



Caractéristiques:

- USB controller with integrated 4-channel sound card for DJs
- Play, mix and scratch digital audio like vinyl records
- 2 decks with selectable source: PC signal or line/phono
- Applicable for analog mixer operation without PC
- External output options for PA applications (XLR/RCA)
- Compatible to any MIDI controlled audio software, all MIDI controllers can be edited and freely assigned
- Optimized for control of the powerful audio and video mixing software Virtual DJ
- Supplied with Virtual DJ 7 Limited Edition, can be upgraded at discount price
- Integrated plug&play audio interface with high-resolution AD/DA converters (16 bits/48 kHz), applicable for Windows XP/Vista/7 and Mac OS X
- Supports all standard codecs, e.g. MP3, WAV, WMA, OGG, M4A, AAC, AVI, MPEG
- 2 line/phono inputs, switchable
- Adjustable DJ microphone input
- Master output and booth output with separate level controls
- Additional recording output
- Headphones output with level control for direct monitoring
- 2-channel mixer section:
- 3-band EQ, gain control and level fader per channel
- Ultra-smooth crossfader with adjustable curve
- Cue function with 3 hot cues
- Stereo LED level display
- Extra large track encoder for quick music library browsing
- Dual player section:
- Touch-sensitive jog dials with mode selector: pitch bend, scratch, fast search
- Dedicated sync function (auto beatmatching)

Logistique

EAN / GTIN: 4026397418729

Poids: 2,70 kg

Longueur: 0.42 m

Largeur: 0.32 m

Hauteur: 0.12 m

- Master Tempo (tonal pitch remains constant)
- Beat-accurate seamless loop, can be edited
- Effect units with controls for selection and parameters
- Sample players with LED display, and controls for selection and level
- Powered via USB or included PSU
- Incl. USB cable
- Fully functional home version of the software available online under virtualdj.com
- Minimum system requirements PC: Windows XP(SP2)/Vista/7, Pentium IV , 1.6 GHz processor, 1 GB RAM
- Minimum system requirements Mac: OS X 10.4.11, Core Duo, 1.66 GHz processor, 1 GB RAM
- Samplingrate: 48 kHz

Données techniques:

Samplingrate:	48 kHz
Connexions:	Entrée: Line/Phono via 2 x RCA stéréo Sortie: rec. via 1 x RCA stéréo Sortie: Master via 1 x RCA stéréo Sortie: Master via 2 x XLR 3 broches Sortie: Booth via 1 x RCA stéréo
Port USB:	USB 2.0, type B
Convertisseur:	16 bit
Dimension:	Largeur : 36 cm Profondeur : 26 cm Hauteur : 7 cm
Poids:	2,20 kg
Type:	USB MIDI controller
	5 V DC, 500 mA via USB port or
	5 V DC, 1000 mA via supplied PSU
Inputs:	
Line/phono:	2 x stereo RCA, switchable
DJ microphone:	3-pin XLR and 6.3 mm jack, bal.
Outputs:	
Master:	3-pin stereo XLR and stereo RCA
Booth:	stereo RCA
Rec:	stereo RCA
Headphones output:	3.5 mm and 6.3 mm jack, bal.
USB port:	2.0, type B
Converter:	16 bits
Sample rate:	48 kHz
Dimensions:	360 x 260 x 70 mm

Contenu de la livraison: