

OMNITRONIC MSM-111 S PRO shotgun mic

Condenser microphone with ball joint

Réf. : 13030838

GTIN: 4026397259148



L'article n'est plus disponible.

Caractéristiques:

- Designed for live sound reinforcement and broadcasting and in studio or live recording
- Set consisting of a 360° rotatable microphone head and a powering module
- Narrow acceptance angle for long-distance sound pickup
- Excellent sound rejection from the sides and rear of mic
- Low inherent self-noise
- Operates on phantom power
- Incl. foam windscreen

Logistique

EAN / GTIN: 4026397259148

Poids: 0,33 kg

Longueur: 0.24 m

Largeur: 0.11 m

Hauteur: 0.05 m

Données techniques:

Type de micro:	Condensateur
Plage de fréquence:	50 - 18000 Hz
Dimension:	Longueur : 23,8 cm Diamètre : Ø 19 cm
Poids:	0,13 kg
Type:	Condenser (back electret)
Operating principle:	Pressure gradient
Polar pattern:	Line + gradient
Sensitivity at 1 kHz:	10 mV/Pa; -36 dBu (±3 dB/Pa)
Nominal impedance:	250 ohms ±30%

Load impedance:	1250 ohms ±30%
Maximum SPL:	135 dB (THD <0.5% @ 1 kHz)
S/N ratio:	72 dB
Equivalent SPL:	21 dBA
Dynamic:	113 dB
Power supply:	16-52 V DC phantom power
Current consumption:	3.5 mA
Connection:	3-pin XLR
Dimensions (L x W x H):	19 x 19 x 238 mm