

EUROLITE AKKU UP-4 HCL Spot WDMX bk

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Réf. : 41700560

GTIN: 4026397539127



L'article n'est plus disponible.

Caractéristiques:

- Compact and bright
- Equipped with 4 x 12 W HCL (hexacolor LED) in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; W-DMX by Wireless Solution; Télécommande infrarouge
- Déjà préprogrammé pour Light´J; LED PC-Control 512; Light Captain
- Exempt de scintillements
- Avec un Angle de départ de 22°

Appareil

Logistique

EAN / GTIN: 4026397539127

Poids: 3,31 kg

Longueur: 0.22 m

Largeur: 0.20 m

Hauteur: 0.25 m

- Sans fil, flexible et polyvalent
- Durée de fonctionnement jusqu'à 8,5h en fonction du programme utilisé

L'étendue des fournitures

- 1 x Appareil, 1 x télécommande

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	37 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; W-DMX by Wireless Solution; Télécommande infrarouge
Préprogrammé dans:	Light´J; LED PC-Control 512; Light Captain
Projection:	Exempt de scintillements
Angle de départ:	22°
Angle de départ (1/2 pic):	22°
Angle de départ (1/10 pic):	33°
Couleur du boîtier:	Noir
Dimension:	Largeur : 13,8 cm Profondeur : 14,5 cm Hauteur : 19,1 cm
Poids:	2,91 kg
Type de batterie:	1 x Lithium-Ion 14,8 V, 6600 mAh, 97,68 Wh
Batterie:	Durée de fonctionnement jusqu'à 8,5h en fonction du programme utilisé Durée de charge 4,5h
Batterie:	1 x pile bouton 3,0 V CR2025 lithium manganèse intégré
Battery pack type:	Li-ion 14.8 V, 6600 mAh (97.68 Wh)
Battery operation:	8.5 hours
Recharging time:	4.5 hours
Battery remote control:	CR2025 button cell 3 V
DMX channels:	6/8/12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
LED type:	12 W HCL
LED number:	4
Beam angle:	22°
Dimensions (L x W x H):	145 x 138 x 191 mm
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle