

## FUTURELIGHT Émetteur-récepteur sans fil DMX WDS-G4 Duo TX

Récepteur sans fil DMX avec technique de Wireless Solution

Réf. : 51834024

GTIN: 4026397631968



**L'article n'est plus disponible.**

### Caractéristiques:

- Two W-DMX transceivers by Wireless Solution in one housing
- Switching between transmitter and receiver
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to AFHSS (Automatic Frequency Hopping Spread Spectrum) technology, interference-free operation also alongside other wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 receivers can be controlled by each transmitter
- Simultaneous operation of up to 6 transmitters, thus control of 3072 DMX channels (6 DMX universes) possible
- LED indication for operation and functions
- 2.4 GHz - license-free worldwide
- Peut recevoir et traiter jusqu'à 1024 canaux DMX
- Peut envoyer jusqu'à 1024 canaux DMX
- (19") 48,3 cm installation en rack 1 HE
- Commandé via DMX; W-DMX by Wireless Solution; plug and play
- A une portée de jusqu'à 500m par visibilité
- 2,4 GHz sans inscription et sans frais dans le monde entier
- Jusqu'à 6 émetteurs peuvent être exploitées en parallèle sans interférences
- Latence extrêmement faible

### Logistique

EAN / GTIN: 4026397631968

Poids: 2,35 kg

Longueur: 0.54 m

Largeur: 0.20 m

Hauteur: 0.08 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 4 W

|                           |                                                                                                                                                        |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type de protection:       | IP20                                                                                                                                                   |
| Branchement électrique:   | Alimentation électrique via P-Con (bleu), version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison)<br>Tramite |
| Canaux DMX:               | Entrée 1024<br>Sortie 1024                                                                                                                             |
| Entrée DMX:               | 2 x XLR (M) 3 broches version encastrable                                                                                                              |
| Sortie DMX:               | 2 x XLR (F) 3 broches version encastrable                                                                                                              |
| Commande:                 | DMX; W-DMX by Wireless Solution; plug and play                                                                                                         |
| Portée:                   | Jusqu'à 500m par visibilité                                                                                                                            |
| Bande de fréquences:      | 2,4 GHz                                                                                                                                                |
| Fréquence porteuse:       | 2,4 GHz                                                                                                                                                |
| Fonctionnement parallèle: | Max. 6 Émetteur                                                                                                                                        |
| Latence:                  | < 5 ms                                                                                                                                                 |
| Modulation:               | AFHSS                                                                                                                                                  |
| Couleur:                  | Noir                                                                                                                                                   |
| Conception du boîtier:    | (19") 48,3 cm installation en rack 1 HE                                                                                                                |
| Dimension:                | Largeur : 48,3 cm<br>Profondeur : 16 cm<br>Hauteur : 4,45 cm                                                                                           |
| Poids:                    | 1,98 kg                                                                                                                                                |