

FUTURELIGHT PHS-150 PRO-Head Spot

Medium moving head

Réf. : 51838155

GTIN: 4026397169966



Caractéristiques:

- 8 brilliant, dichroic colors plus white
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 6 rotating gobos plus open
- All gobos can be interchanged
- With gobo-shake function
- Exact positioning via 16 bit Pan/Tilt movement resolution
- Manual focus
- Strobe effect with 1-10 flashes per second
- Mechanic dimmer
- PAN-angle switchable between 630° and 540° (depending upon the software version)
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For bright 150 W discharge lamp
- DMX control via every standard DMX controller
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Logistique

EAN / GTIN: 4026397169966

Poids: 17,30 kg

Longueur: 0.56 m

Largeur: 0.42 m

Hauteur: 0.46 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	285,00 W
DMX channels:	10
DMX connection:	3-pin XLR
Flash-rate:	10 Hz
Color-wheel:	8 dichroic filters and open
Rotating gobo-wheel:	6 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	23 mm
Length of base:	330 mm
Width of yoke:	320 mm
Height (head horizontal):	485 mm
Weight:	13 kg
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

Contenu de la livraison:
