

FUTURELIGHT DMH-150 LED Moving Head

High performance LED moving head with 150 W COB LED

Réf. : 51841970

GTIN: 4026397474534



Caractéristiques:

- Equipped with a 150 W COB LED - comparable to a 575 W discharge lamp
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- 21, 23 or 24 DMX channels selectable (up to software version 1.1.00)
- 14, 16, 21 or 24 DMX channels selectable (from software version 1.1.01)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Gobo wheel 2 with 7 static gobos plus open
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Autofocus
- Steplessly adjustable iris
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset

Logistique

EAN / GTIN: 4026397474534

Poids: 16,15 kg

Longueur: 0.52 m

Largeur: 0.43 m

Hauteur: 0.36 m

- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Commandé via commande de la musique via microphone; DMX; RDM

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	210 W
Mouvement de basculement max. TILT:	270° positionnement
Mouvement de pivotement max. PAN:	630° positionnement
Gobos:	Diamètre externe 27mm Diamètre de l'image 22mm
Canaux DMX:	21
Commande:	Commande de la musique via microphone; DMX; RDM
Fixtures disponibles pour:	Light Captain
Angle de départ (1/2 pic):	14°
Couleur:	Noir
Dimension:	Largeur : 34,3 cm Profondeur : 25 cm Hauteur : 42,8 cm
Poids:	14,10 kg
DMX channels:	21/23/24 (up to software version 1.1.00)
DMX channels:	14/16/21/24 (from software version 1.1.01)
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
LED type:	Array 150 W
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Static gobo-wheel:	7 gobos and open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

Contenu de la livraison:
