

MADRIX AURA 12

Advanced lighting-control recorder and stand-alone playback unit for 6144 channels

Réf. : 51860394

GTIN: 4260263421325



Caractéristiques:

- Can transmit up to 6144 DMX channels
- The device is cooled by passive convection cooling
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; stage; restaurants, bars and hotels; architecture
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistique

EAN / GTIN: 4260263421325

Poids: 0,34 kg

Longueur: 0.20 m

Largeur: 0.14 m

Hauteur: 0.07 m

Données techniques:

Power supply:	12/24V DC
Power consumption:	1.5 W
IP classification:	IP20
Power connection:	Mains input via special connector recessed mounting Mains input via USB, type B
DMX channels:	Output 6144
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s Protocol: Streaming ACN (sACN / ANSI E1.31) via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s
Cooling:	Passive convection cooling

Connections:	Network connection via 2 x RJ-45 (F) mounting version
USB port:	Type B
Weight:	0.19 kg

Contenu de la livraison:

- 1 x device
- 1 x user manual
- 1 x network cable
- 2 x fixation clip
- 1 x terminating plug (power)