

REUTLINGER Cable glider type 50SVII-ZW M12i bk

Support de câble métallique, charge de 130 kg max.

Réf. : 58010573

GTIN: 4026397565850



L'article n'est plus disponible.

Description:

Certified cable holder

Cable holders can be used for easily suspending static workloads on attachment ropes. No tools are required. The load can be hung at any position and height and easily be re-positioned.

The REUTLINGER cable holders are the only system certified by two independent certification bodies. This cable holder boasts of a TÜV certificate and a German BGV C1 certificate and can be used in entertainment technology.

TÜV GS and BGV C1 - double-tested and double-certified

REUTLINGER® grippers type 50 SV II, type 66 and type 80 SV II are not only certified as safe (GS) by the German TÜV, they have also been licensed for use within the scope of standard DGUV Regulation 17 (BGV C1).

The DGUV Test certificate authorises these grippers for use within the scope of the accident prevention regulations issued by the German employers' liability insurance associations in respect of staging and production facilities.

The test seal of the DGUV is conferred only after extensive examining of all load applications.

Further testing simulated most anticipated mis-applications.

REUTLINGER® gripper ranges 50, 66 and 80 are the only load-bearing devices certified by the DGUV for use in mobile production facilities.

Logistique

EAN / GTIN: 4026397565850

Poids: 0,26 kg

Longueur: 0.10 m

Largeur: 0.03 m

Hauteur: 0.03 m

Caractéristiques:

- For rope diameters 4.0 to 5.0 mm
- 6-ball mechanism
- With side exit hole
- TÜV-GS
- German BG certificate

- Please note: Cable gliders must not be used for dynamic loads. Always use at least 2 cable gliders for every suspended object.
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Pour diamètre de corde:	4 mm - 5 mm
Charge de travail:	5 mm: 130 kg 4 mm: 80 kg
Couleur:	Noir
Dimension:	Longueur : 6,90 cm Diamètre : Ø 2,50 cm
Poids:	0,25 kg
Workload 4 mm:	80 kg
Workload 5 mm:	130 kg
Diameter:	25 mm
Thread:	M12
Thread length:	8 mm
Length:	69 mm