

## EUROLITE ESN 7x80 5mm LED red/green/yello

Message mouvant PRO

Réf. : 80500106  
GTIN: 4026397271621



## L'article n'est plus disponible.

### Description:

In fields of advertising and information, electronic signs and moving messages respectively, become more and more popular. And this is not next door to a miracle if you look at the spectrum of possibilities. The different units of the ESN-series are not only able to show 93 standard characters in 14 fonts, to attract attention, the moving messages are also equipped with various display effects. These effects are performed in six diverse speeds. Furthermore, with the option to get signs programmed via a network, the series offers a real handy advantage.

### Caractéristiques:

- Large-scale information board for indoors and protected areas
- Ideal for welcome, announcements, special events, orientation etc.
- With 5-mm-LEDs for ideal readability from up to 25 meters distance
- Color and background color freely selectable via red/green/yellow LEDs
- High resolution with 54 mm character height per display line
- Single-line display with up to 13 visible characters
- 93 standard characters (letters/numbers) capitalized/small letters, symbols and language specific characters
- 14 fonts, 13 more fonts can be imported
- Fonts-manager for selecting different fonts, font sizes, letter cutting (bold) and for completely redesigning fonts
- Flash adjustable for emphasizing the message
- 50 different display effects (e.g. scroll up) freely selectable for In Mode and Out Mode
- 6 different speeds adjustable
- Display time of the message adjustable between 0 and 60 seconds
- Playlists of individual messages programmable

### Logistique

EAN / GTIN: 4026397271621  
Poids: 2,85 kg  
Longueur: 0.81 m  
Largeur: 0.11 m  
Hauteur: 0.16 m

- With Timer-function (operation intervals and ignore times freely programmable)
- Permanent Flash-memory with 1 GB capacity
- Easy installation and comfortable operation via remote control (optional)
- Installation clamps and wall mounting included in the delivery
- Software-CD included in the delivery for comfortable programming
- Time display in different formats (24 h, 12 h AM/PM, seconds, time zone)
- Date in different styles (DD.MM.YYYY, US/UK or MM.DD.YYYY)
- Selection of year, month or day of the week in letters or numbers
- Freely programmable graphic-patterns via Picture Manager
- Net Manager for operating several Moving Messages
- Interfaces via RS232 (serial) or Ethernet (TCP/IP-protocol)
- RS232-connection via RJ11 plug and 9-pin SUB-D socket
- 10 m data-cable for RS232-connection included in the delivery
- RS232-connection extendable to max. 20 m (optional)
- IP-address for Ethernet-control freely programmable
- Minimum system-requirements): CPU 500 MHz or higher, VGA-card with small font, 128 MB memory, 10 MB of free hard disc space, CD-Rom drive, free COM-port or Ethernet-port, Windows 9X or higher, mouse, monitor refresh rate 60 Hz or higher
- 560 LED puissantes 5 mm R/G/Y
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via Câble réseau; Télécommande infrarouge (non incluse dans la livraison)

#### L'étendue des fournitures

- 1 x Appareil, 1 x CD, 1 x bloc d'alimentation externe, 1 x Câble secteur/câble d'alimentation, 1 x Câble réseau, 1 x câble adaptateur, 2 x matériel de fixation, 2 x angle, 4 x vis, 1 x Mode d'emploi

#### Données techniques:

|                                   |                                                                                                                                                    |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentation électrique:          | 100-240 V CA, 50/60 Hz<br>5V CC 1000 mA                                                                                                            |
| Puissance totale de raccordement: | 15,00 W                                                                                                                                            |
| Type de protection:               | IP20                                                                                                                                               |
| Classe de protection:             | SK III                                                                                                                                             |
| Branchement électrique:           | Alimentation électrique via fiche creuse (M)<br>version encastrable câble d'alimentation à prise<br>euro (inclus dans la livraison)<br><br>Tramite |
| Longueur du câble:                | Max. 20 m                                                                                                                                          |
| Batterie:                         | 2 x 1,5 V AA Mignon LR06 alcaline au<br>manganèse ci-joint                                                                                         |
| Type de LED:                      | 560 x 5 mm R/G/Y                                                                                                                                   |
| Connexion au réseau:              | Protocole : Ethernet TCP/IP via 1x RJ-45 (F)<br>version encastrable                                                                                |
| Refroidissement:                  | Refroidissement par convection passive                                                                                                             |
| Commande:                         | Câble réseau; Télécommande infrarouge (non<br>incluse dans la livraison)                                                                           |
| Image:                            | Max. 7x80 px<br>%                                                                                                                                  |
| Présentation:                     | 1-à lignes, 13 caractères visibles<br>8 couleurs 4 couleurs de fond                                                                                |
| Texte:                            | 93 avec chacun 2000 caractères<br>14 typographies<br>120 symboles                                                                                  |
| Couleur du boîtier:               | Noir                                                                                                                                               |
| Connexions:                       | RS 232 via RJ11 (F) version encastrable<br>RS 485 via RJ11 (F) version encastrable                                                                 |

|                           |                                                           |
|---------------------------|-----------------------------------------------------------|
| Écran:                    | 61 cm x 5,5 cm                                            |
| Dimension:                | Largeur : 66 cm<br>Profondeur : 5 cm<br>Hauteur : 10,2 cm |
| Poids:                    | 2,50 kg                                                   |
| Spécifications juridiques |                                                           |
| Produit spécial:          | Non destiné à l'éclairage de la pièce dans les ménages    |
| Utilisation:              | Éclairage pour effets de spectacle                        |