

OMNITRONIC Set OMNITRONIC Budget II

Art.n.: 09000074

GTIN:



L'articolo non è più disponibile.

Features :

OMNITRONIC SMA-600 Amplifier

Stereo PA amplifier with limiter and SMPS, 2 x 300 W/4ohms

- Low weight and height due to integrated switch-mode power supply
- Temperature-controlled fan, particularly quiet during operation
- Limiter and speaker switch-on delay
- Switchable bass-boost at 80 Hz with 6 dB level increase
- 3 operating modes can be selected (stereo, parallel or bridged)
- Selectable input sensitivity
- 2 level controls
- 3 LEDs for each channel for activated protective circuit (protect) overload (clip) and signal
- 2 LEDs for parallel and bridge operation
- Complete protection set against short-circuit, overheat, DC voltage and VHF signals
- Electronically balanced inputs via XLR mounting jacks, with feed-through output (stereo RCA/6.3 mm jack)
- Speaker outputs via lockable Speaker plugs
- Class AB circuitry
- Robust steel chassis
- Rack installation with 2 units
- Montaggio su rack (19") 48,3 cm

OMNITRONIC C-80 black 2x

Passive 2-way speaker pair with mount, 8" woofers and 85 W RMS

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass

Logistica

- 20 cm woofer (8") and 2.5 cm dome tweeter (1")
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.

OMNITRONIC Subwoofer for Control Systems

Passive subwoofer with crossover, 6,5" woofer, 50 W RMS / 4 ohms

- The completion for your Control system
- Can be used for Control 1, Control 5, Control 100 and Control 200
- Stereo connection via screw connector
- Built-in crossover separates at 300 Hz
- High efficiency
- 16.5 cm woofer (6.5") in bandpass enclosure
- Bass-reflex tube with a diameter of 6 cm

Dati tecnici :

Peso:	26,45 kg
-------	----------

OMNITRONIC SMA-600 Amplifier

Alimentazione elettrica:	230 V AC, 50 Hz
--------------------------	-----------------

Potenza totale installata:	421,00 W
----------------------------	----------

Potenza in uscita:	Massimo 648 W 2 x 324 W RMS (4 Ohm) 2 x 231 W RMS (8 Ohm)
--------------------	---

Commutazione:	Class H
---------------	---------

Struttura della custodia:	Montaggio su rack (19") 48,3 cm
---------------------------	---------------------------------

Misure:	Larghezza: 48,3 cm Profondità: 34 cm Altezza: 8,9 cm
---------	--

Peso:	5,75 kg
-------	---------

Power output sine:	
--------------------	--

stereo 4 ohms	2 x 324 W
---------------	-----------

stereo 8 ohms	2 x 231 W
---------------	-----------

8 ohms bridged	1 x 600 W
----------------	-----------

Frequency range:	20-20000 Hz, ± 0.5 dB
------------------	---------------------------

Damping factor:	>150
-----------------	------

Distortion factor:	0.05 %
--------------------	--------

Slew rate:	>20 V/ μ sec
------------	------------------

S/N ratio:	>90 dB
------------	--------

Channel separation:	>65 dB/ 1 kHz
---------------------	---------------

Input sensitivity:	26 dB/32 dB (2.2 V/1.05 V), switchable
--------------------	--

Voltage gain:	26 dB/32 dB
---------------	-------------

Input impedance:	20 kohms (balanced), 10 kohms (unbalanced)
------------------	--

Input connectors:	stereo XLR
-------------------	------------

Output connectors:	stereo Speaker, feed-through output (stereo RCA, stereo 6.3 mm jack)
Circuitry:	class AB
Control elements:	power switch, level control per channel, mode switch (stereo/parallel/bridged), sensitivity selector, peak filter selector
LED indicators:	parallel, bridge (globally), protect, clip, signal (per channel)
Protection circuits:	short-circuit, overheat, DC voltage, VHF signals, softstart
Construction:	steel chassis
Dimensions (DxWxH):	340 x 483 x 92 mm (19", 2 U)

OMNITRONIC C-80 black 2x

Capacità di carico:	Programma: 125W Nominale: 85W RMS
Intervallo di frequenza:	50 - 20000 Hz
Sensibilità:	90 dB (1W/1m)
Impedenza:	8 Ohm
Collegamenti:	Ingresso: Altoparlante via terminale a vite
Altoparlante:	1 x 8" Woofer 1 x tweeter
Colore:	Nero
Misure:	Larghezza: 27 cm Profondità: 24 cm Altezza: 36 cm
Peso:	11,70 kg
Komponenten:	20 cm woofer (8"), 2.5 cm tweeter (1")
Connection:	2-pole terminal
Sensitivity:	90 dB
Dimensions (H x W x D):	360 x 270 x 240 mm

OMNITRONIC Subwoofer for Control Systems

Capacità di carico:	Programma: 150W Nominale: 50W RMS
Intervallo di frequenza:	50 - 130 Hz
Sensibilità:	85 dB (1W/1m)
Pressione acustica massima:	91 dB
Collegamenti:	Ingresso: Altoparlante via morsetto a molla
Altoparlante:	1 x 6,5" Woofer
Colore:	Nero
Misure:	Larghezza: 35 cm Profondità: 42 cm Altezza: 25 cm
Peso:	9 kg

Components:	16.5 cm woofer (6.5")
Connection:	stereo / 2-pole terminals
Sensitivity:	85 dB
Maximum SPL:	91 dB