

## OMNITRONIC PM-3010B Pro DJ mixer

PRO 3+1-channel DJ mixer with matrix

Art.n.: 10006851

GTIN: 4026397313055



**L'articolo non è più disponibile.**

### Features :

- Matrix input assignment: each channel with routing facility of all input sources as desired
- 3 channels with gain control, 3-band equalizer, cue button, smooth and durable fader and 10-digit LED level meter
- 1 DJ microphone channel with 3-band equalizer, level control, on air and talkover selector
- Color illuminated rotary controls and rubber buttons
- Prefader listening to all input channels and the master output via adjustable headphones output, with cue mix/split function
- Replaceable crossfader with VCA technology for crossfading between input channels, with assignment switches, adjustable curve and reverse function
- Master control and stereo LED level meter
- Master level switchable 0.75 V or 1.5 V
- Separately controllable monitor and zone outputs
- Separately controllable session output to connect a further mixer
- 2 recording outputs, independent of the master and with on/off switch for DJ microphone signals
- Inputs: 4 x line (stereo RCA); 3 x phono/line (stereo RCA), switchable; 1 x DJ microphone (XLR/6.3 mm jack), 2 x microphone (6.3 mm jack) and 1 x headphones (6.3 mm jack)
- Outputs: 1 x master (stereo XLR/stereo RCA), 1 x zone (6.3 mm stereo jack, bal.), 1 x booth (stereo RCA), 2 x record (stereo RCA) and 1 x session (stereo RCA)
- Operation via supplied power unit

### Logistica

EAN / GTIN: 4026397313055

Peso : 5,00 kg

Lunghezza : 0.47 m

Larghezza : 0.28 m

Altezza : 0.17 m

### Dati tecnici :

Potenza totale installata: 35,00 W

Intervallo di frequenza: 20 - 20000 Hz

|                               |                                                         |
|-------------------------------|---------------------------------------------------------|
| Misure:                       | Larghezza: 34 cm<br>Profondità: 22 cm<br>Altezza: 11 cm |
| Peso:                         | 4,55 kg                                                 |
| Power supply:                 | 230 V AC, 50 Hz,<br>via supplied power unit             |
| Inputs:                       |                                                         |
| DJ microphone:                | combined XLR/6.3 mm jack (1/4") (bal.)                  |
| MIC 1, 2:                     | 6.3 mm jack (1/4") (bal.)                               |
| Minimum input voltage:        | 1 mV RMS                                                |
| LINE/PHONO 1-3:               | stereo RCA                                              |
| Minimum input voltage:        | 150 mV RMS (line), 3 mV RMS (phono)                     |
| AUX 1-4:                      | stereo RCA                                              |
| Minimum input voltage:        | 150 mV RMS                                              |
| Outputs:                      |                                                         |
| MASTER:                       | stereo XLR/stereo RCA                                   |
| Output voltage:               | 0.75 V/1.5 V RMS (switchable)                           |
| ZONE:                         | 6.3 mm stereo jack                                      |
| Output voltage:               | 0.75 V RMS                                              |
| BOOTH:                        | stereo RCA                                              |
| Output voltage:               | 0.75 V RMS                                              |
| REC:                          | stereo RCA                                              |
| Output voltage:               | 0.75 V RMS                                              |
| Headphones output:            | 6.3 mm jack (min. 8 ohms)                               |
| Tone control (DJ microphone): |                                                         |
| 1 x high:                     | -12 dB to +12 dB/ 10 kHz, ±1 dB                         |
| 1 x middle:                   | -12 dB to +12 dB/ 1 kHz, ±1 dB                          |
| 1 x low:                      | -12 dB to +12 dB/ 100 Hz, ±1 dB                         |
| Talkover attenuation:         | -15 dB                                                  |
| Tone control (channel 1-3):   |                                                         |
| 3 x high:                     | -26 dB to +12 dB/ 10 kHz, ±1 dB                         |
| 3 x middle:                   | -26 dB to +12 dB/ 1 kHz, ±1 dB                          |
| 3 x low:                      | -26 dB to +12 dB/ 100 Hz, ±1 dB                         |
| S/N ratio:                    | >75 dB                                                  |
| Distortion:                   | 0.03%                                                   |
| Dimensions (WxHxD):           | 340 x 220 x 110 mm                                      |