

OMNITRONIC MZD-860 Matrix Zone Distributor

8-channel mixer with 6 outputs and matrix

Art.n.: 10304115

GTIN: 4026397374254



Descrizione :

The OMNITRONIC MZD-860 is a matrix zone distributor of 6 inputs for units with line level (e.g. CD player) and microphones (also phantom-powered) which are freely assignable to each of the 6 outputs. A further stereo line channel connects four units with line level and allows for free assignment. Thus it's possible to supply 6 different PA zones with a mono output by routing different input signals to these zones without having to change the cable configuration. It's also possible to obtain 6 outputs with different mixing as every input has its own level control.

Features :

- 6 microphone/line channels, switchable at the front, with separate gain controls, 2-band equalizer, level control and clip LED
- 1 stereo line channel with 4-way input selector, gain control, 2-band equalizer, level control and clip LED
- Matrix input assignment: each input channel is freely assignable to each of the 6 outputs
- Each microphone input with low-noise preamplifier and optional +48 V phantom power
- 6 mono outputs with level control and 6-digit LED level meter
- Color illuminated buttons
- Inputs: 6 x line (stereo RCA), 6 x microphone (XLR), 4 x aux (stereo RCA)
- Outputs: 6 x master (optionally XLR or RCA)
- Rack installation, 3 U
- Montaggio su rack (19") 48,3 cm 3 U

Logistica

EAN / GTIN: 4026397374254

Peso : 5,40 kg

Lunghezza : 0.55 m

Larghezza : 0.26 m

Altezza : 0.21 m

Dati tecnici :

| | |
|----------------------------|--|
| Alimentazione elettrica: | 230 V AC, 50 Hz |
| Potenza totale installata: | 15,00 W |
| Allacciamento elettrico: | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Intervallo di frequenza: | 20 - 20000 Hz |
| Struttura della custodia: | Montaggio su rack (19") 48,3 cm 3 U |
| Misure: | Larghezza: 48,3 cm Profondità: 200 cm Altezza: 13,35 cm |
| Peso: | 4,75 kg |
| Input impedance: | 20 kohms (XLR), 10 kohms (RCA) |
| Output impedance: | 300 ohms (XLR), 150 ohms (RCA) |
| Input gain: | +12 dB to +60 dB (mic), 0 dB to +12 dB (line) |
| Channel level: | ~ to +6 dB/ 0.5 dB |
| Output level: | ~ to +6 dB/ 0.5 dB |
| 7 x EQ treble: | ±12 dB |
| 7 x EQ low: | ±12 dB |
| S/N ratio: | 75 dB (mic), 85 dB (line) |
| THD: | 1% (mic), 0.05 % (line) |

Contenuto della confezione: