

## OMNITRONIC GEQ-215B Equalizer 2x15-band

2 x equalizzatore grafico a 15 bande

Art.n.: 10355521

GTIN: 4026397360370



**L'articolo non è più disponibile.**

### Features :

- 2-channel version, 2 x 15 frequency controls with 2/3 octave steps
- Short sliding frequency controls with center click
- EQ gain switchable  $\pm 6$  dB to  $\pm 15$  dB
- Switchable low cut filter
- Separate level control per channel
- Bypass switch allows instant comparison of the original sound with the equalized sound
- 7-fold LED level meter with clip indicator
- Inputs and outputs via 6.3 mm jack sockets (1/4") and XLR sockets
- Groundlift switch
- Rack installation, 1 U

### Logistica

EAN / GTIN: 4026397360370

Peso : 3,15 kg

Lunghezza : 0.55 m

Larghezza : 0.25 m

Altezza : 0.08 m

### Dati tecnici :

|                            |                                                               |
|----------------------------|---------------------------------------------------------------|
| Alimentazione elettrica:   | 230 V AC, 50 Hz                                               |
| Potenza totale installata: | 10,00 W                                                       |
| Equalizzatore:             | 2 x equalizzatore grafico a 15 bande                          |
| Misure:                    | Larghezza: 48,3 cm<br>Profondità: 17,5 cm<br>Altezza: 4,45 cm |
| Peso:                      | 2,60 kg                                                       |
| Input impedance:           | 10/20 kohms (unb./bal.)                                       |

|                         |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| Output impedance:       | 300/150 kohms (unb./bal.)                                         |
| In/Out connectors:      | XLR, jack                                                         |
| S/N ratio:              | >95 dB                                                            |
| Crosstalk:              | >90 dB                                                            |
| Distortion:             | <0.01 %                                                           |
| Frequency range:        | 20-20000 Hz, $\pm 0.5$ dB                                         |
| Output level:           | - $\infty$ to +6 dB                                               |
| Control range:          | $\pm 6$ dB or $\pm 15$ dB                                         |
| Frequencies:            | 2 x 25/40/63/100/160/250/400/630 Hz,<br>1/1.6/2.5/4/6.3/10/16 kHz |
| Low Cut:                | 30 Hz, -3 dB                                                      |
| Dimensions (W x D x H): | 483 x 175 x 44 mm                                                 |