

## OMNITRONIC DXO-26 PRO Digital controller

Digital stereo active crossover incl. PC software

Art.n.: 10356350

GTIN: 4026397177770



**L'articolo non è più disponibile.**

### Features :

- 2 analog inputs and 6 analog outputs (servo-balanced XLR connectors)
- Active frequency filter with slopes up to 48 dB/octave split up the audio signal into different frequency bands
- MIDI interface
- Rs232 interface, compatible to PCs
- Incl. software editor for remote control via PC: store, transfer, and manage your presets
- 60 user programs can be memorized internally or via PC software
- Both inputs or a sum of both can be split up into a maximum of 6 frequency bands
- Up to 38 frequency bands for fine-tuning the frequency range adjustable
- Up to 635.417 ms total delay for the inputs and outputs adjustable
- Delay displayed in milliseconds, meters, feet and frame/second
- Output limiter with adjustable limits and automatic attack and release settings as overload protection for your amplifying system
- Lock function for protecting the program settings
- Phase Invert switch per output
- Switch-mode power supply
- Rack installation, 1 U

### Logistica

EAN / GTIN: 4026397177770

Peso : 3,80 kg

Lunghezza : 0.52 m

Larghezza : 0.33 m

Altezza : 0.08 m

### Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Potenza totale installata: 30,00 W

Misure: Larghezza: 48,3 cm

Profondità: 22,3 cm

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
|                       | Altezza: 4,45 cm                                                     |
| Peso:                 | 3,6 kg                                                               |
| Inputs:               | 2, active, balanced                                                  |
| Gain range:           | ±15 dB                                                               |
| Input impedance:      | 10 kohms                                                             |
| Frequency range:      | 15-20000 Hz, ±0.25 dB                                                |
|                       | 15-40000 Hz, ±3 dB                                                   |
| Outputs:              | 6, active, balanced with automatic correction for unbalanced loading |
| Output impedance:     | <50 mohms (electronically balanced)                                  |
| Output gain range:    | ±21 dB                                                               |
| Maximum output level: | +20 dBu                                                              |
| Frequency range:      | 15-20000 Hz, ±0.25 dB                                                |
|                       | 15-40000 Hz, ±3 dB                                                   |
| Distorsion:           | 0,005 %, 20-20000 Hz                                                 |
| S/N-ratio:            | 112 dB (22-22000 Hz)                                                 |
| Channel separation:   | 80 dB (30-20000 Hz)                                                  |
| Filter:               |                                                                      |
| Slopes:               | 6, 12, 18, 24 or 48 dB/Oktave                                        |
| Type:                 | Bessel, Butterworth or Linkwitz-Riley                                |
| Crossover frequency:  | 15-20000 Hz                                                          |
| Delay:                | 0~635.417 ms                                                         |
| Dimensions (WxHxD):   | 482 x 44 x 223 mm                                                    |