

## OMNITRONIC L-300, Amplifier 2x150W/4 ohm

Reliable PA amplifier for starters

Art.n.: 10450670

GTIN: 4026397243062



**L'articolo non è più disponibile.**

### Features :

- 2 x 150 W/4 ohms
- Enormous power with highest brilliance
- 2 gain controls on the frontpanel
- All operation modes controllable via LEDs
- Signal inputs via XLR female or 6.3 mm jack socket
- Speaker connection via lockable Speaker plugs
- Ground lift switch against humming
- Bridged switch for bridging
- Protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation

### Logistica

EAN / GTIN: 4026397243062

Peso : 9,70 kg

Lunghezza : 0.51 m

Larghezza : 0.42 m

Altezza : 0.10 m

### Dati tecnici :

|                            |                                                             |
|----------------------------|-------------------------------------------------------------|
| Potenza totale installata: | 650,00 W                                                    |
| Potenza in uscita:         | 75 W RMS (8 Ohm)                                            |
| Intervallo di frequenza:   | 10 - 50000 Hz                                               |
| Misure:                    | Larghezza: 48,3 cm<br>Profondità: 35 cm<br>Altezza: 4,45 cm |
| Peso:                      | 8,70 kg                                                     |
| Power supply:              | 115/230 AC V AC, 50/60 Hz                                   |

Power output (RMS):

|                            |                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------|
| Stereo 4 ohms              | 2 x 150 W                                                                           |
| Stereo 8 ohms              | 2 x 75 W                                                                            |
| 8 ohms bridged             | 1 x 300 W                                                                           |
| Signal-to-noise ratio:     | >100 dB                                                                             |
| Total harmonic distortion: | 0.05 %                                                                              |
| Damping factor:            | >150                                                                                |
| Slew rate:                 | 70 V/μsec.                                                                          |
| Crosstalk:                 | >70 dB                                                                              |
| Input impedance:           | 20 kohms                                                                            |
| Input connectors:          | 2 x XLR, 2 x Jack mounting socket                                                   |
| Output connectors:         | 2 x Speaker                                                                         |
| Protection:                | Overheat, overload, short-circuit, DC, softstart                                    |
| Cooling:                   | Temperature-controlled fan                                                          |
| Controls:                  | Power switch, input attenuators, Mode switch - Stereo/Parallel/Bridged, Ground Lift |
| Indicators:                | Power, Clip, Protect, Parallel, Bridge                                              |
| Construction:              | Steel chassis, aluminum front panel                                                 |
|                            | Rack installation with 1 u                                                          |