

OMNITRONIC CMP-2000 Dual CD/MP3 Player

Dual CD player with MP3 function for DJs

Art.n.: 10602409

GTIN: 4026397478457



Features :

- Audio CD, CD-R, CD-RW, MP3 CD
- 2 USB ports for storage media and portable players (FAT 32)
- Easy Source Select: route USB sources to both drives as desired
- Combined Device Access: both drives can access the same USB medium simultaneously
- Access music files more easily and quickly via smart music database management with free PC software Database Builder
- Sort USB devices lightning-fast by title, artist, album and genre
- System menu for user-defined settings
- 2 x 20 seconds anti-shock protection
- Outstanding reading time of the files (instant start within 10 ms)
- Automatic beat counter (switchable to manual operation)
- Master tempo (tonal pitch remains constant when speed is changed)
- 2 alphanumeric LCDs with ID3 tag indication
- Touch-sensitive jog dials with adjustable sensitivity and mode selector: scratch or pitch bend
- Pitch adjustment $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ (MP3 CD $\pm 16\%$)
- Fader start
- Relay function
- Folder navigation
- Pitch Bend
- Cue/auto cue function
- Seamless loop/reloop
- Single or continuous play
- Repeat function
- Indication of elapsed time, remain time (MP3 files) or total remain time (audio CD)
- Bargraph display
- Pitch adjustment is displayed in %

Logistica

EAN / GTIN: 4026397478457

Peso : 7,90 kg

Lunghezza : 0.45 m

Larghezza : 0.18 m

Altezza : 0.54 m

- Extra-large play/pause and cue buttons with color illumination
- Drives are locked in play mode
- Rack installation
- The Database Builder software is available in the manufacturer's download section
- Processore di segnale digitale master tempo
- Frequenza di campionamento: 44,1 kHz
- Impostazione del passo: CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$
- Impostazione del passo: MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$

Modulo di comando

- Montaggio su rack (19") 48,3 cm 2 U
audioplayer
- Montaggio su rack (19") 48,3 cm 2 U

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	16,00 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Intervallo di frequenza:	17 - 20000 Hz
Rapporto segnale-rumore:	>126 dB
Distorsione armonica totale:	<0,008 % a 1 kHz
DSP:	Processore di segnale digitale master tempo
Audioplayer:	USB + lettore CD, (ID3 tag), Anti-shock, Seamless loop
Frequenza di campionamento:	44,1 kHz
Dispositivo CD:	Cassetto-disco doppio
Schermo:	ID3-Tags , Tempo di riproduzione del titolo , Tempo residuo del titolo , Tempo di gioco residuo totale
Collegamenti:	Uscita: 2 x RCA stereo
Formato musicale:	CD, CD-R, CD-RW, CD-DA, MP3
Accuratezza del fotogramma:	1/75 s
Supporti di memorizzazione appropriati:	Periferica USB max. 32GB (FAT 32)
Impostazione del passo:	CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$
Collegamento USB:	2 x type A
Convertitore:	8-fach/ 1 bit
Peso:	6,80 kg
Struttura della custodia:	Montaggio su rack (19") 48,3 cm 2 U
Misure:	Larghezza: 48,3 cm Profondità: 26,5 cm Altezza: 8,9 cm
Struttura della custodia:	Montaggio su rack (19") 48,3 cm 2 U
Misure:	Larghezza: 48,3 cm Profondità: 9,5 cm Altezza: 8,9 cm

Contenuto della confezione:

1 x audioplayer

1 x Modulo di comando