

OMNITRONIC DD-2520 USB Turntable bk

Direct-drive DJ turntable with switchable phono/line output

Art.n.: 10603060

GTIN: 4026397295009



Descrizione :

Direct-driven record player with phono/line switch

Digitize your old vinyl treasures in a few steps with the direct-driven turntable Omnitronic DD-2520 USB.

Copying is a child's play

Thanks to the integrated USB interface and software you can record your favorite vinyls on your PC. You don't need any drivers, the player is identified automatically. A phono pre-amp is inbuilt and helps you to digitize your music without the need of additional hifi amps or DJ mixers.

Phono/line switch

You can also simply play and enjoy your records with the DD-2520. The switchable phono/line output enables you to connect the player to almost any sound system with phono or line input.

Fully-fledged DJ turntable

As the DD-2520 shows a precision drive, a rugged housing and shock-absorbing feet, it is perfectly suited to as player in your DJ set at home.

Logistica

EAN / GTIN: 4026397295009

Peso : 12,50 kg

Lunghezza : 0.53 m

Larghezza : 0.41 m

Altezza : 0.20 m

Features :

- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Driver installation not required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- Precision direct drive

- Delivery includes pick-up system
- 2 speeds, pitch control $\pm 10\%$
- Large start/stop button
- Strobe lamp for exact speed adjustment
- Target lamp
- Delivery includes removable dustcover
- Adjustable anti-skating
- Shock-absorbing feet
- Switchable output phono/line
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Impostazione del passo: $\pm 10\%$
- The device can be connected via USB to the PC

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	12,00 W
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina europea
Intervallo di frequenza:	20 - 20000 Hz
Tipo di trazione:	Direct drive Motore brushless a corrente continua
Azionamento:	Coppia di avviamento: 1 kg/cm Tempo di avviamento: 1 sec. Tempo di decelerazione: 1 sec. Transizione di velocità: <1s 1kHz 5cm/sec
Flutter:	<0,15 % WRMS
Rombo:	55 dB DIN B
Regime:	33 Giri/min; 45 Giri/min
Braccio di riproduzione:	A forma di S con sospensione cardanica Length: 230 Overhang: 16 mm Stylus pressure: 0-4 g, regolabile
Livello di uscita:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Collegamenti:	Uscita: line/phono via RCA stereo Uscita: Versione da incasso USB B (F)
Impostazione del passo:	$\pm 10\%$
Collegamento USB:	1 x USB 1.1, type B
Colore:	Nero
PC connect:	Via USB
Misure:	Larghezza: 45 cm Profondità: 35 cm Altezza: 15,5 cm
Peso:	11,25 kg
Misure:	Diametro: Ø 33 cm

Contenuto della confezione:

- 1 x Sistema
- 1 x Piatti per fonografi