

OMNITRONIC PMS-10 Studio subwoofer

The completion for your studio monitors

Art.n.: 11036468

GTIN: 4026397222517



Features :

- Suitable for PMM-4, PMM-5, PMM-8, PSM-6.5, PSM-6.5A and all other passive systems in need of bass support
- High efficiency
- Stereo input (XLR/6.3 mm jack)
- Stereo output and feed-through output (both XLR)
- Active 2-way crossover
- Level control
- Phase inversion switch
- High-pass filter, selectable via footswitch
- Standby mode

Logistica

EAN / GTIN: 4026397222517

Peso : 17,40 kg

Lunghezza : 0.55 m

Larghezza : 0.53 m

Altezza : 0.44 m

Dati tecnici :

| | |
|----------------------------|---|
| Alimentazione elettrica: | 230 V AC, 50 Hz |
| Potenza totale installata: | 250 W |
| Intervallo di frequenza: | 40 - 350 Hz |
| Collegamenti: | Ingresso: Altoparlante via 1 x XLR a 3 poli Ingresso: Altoparlante via 1 x Jack da 6,3 mm (non sim.) |
| Altoparlante: | 1 x 10" Woofer |
| Misure: | Larghezza: 43 cm Profondità: 43 cm |

| | |
|-------------------------|--------------------|
| | Altezza: 31,5 cm |
| Peso: | 15,50 kg |
| Amplifier power: | 150 W |
| Components: | 25 cm woofer (10") |
| Inputs: | XLR/6.3 mm jack |
| Outputs: | XLR |
| Footswitch: | 6.3 mm jack |
| Distortion factor: | 0.05 % |
| Min. input sensitivity: | 0.775 V |
| Input impedance: | 4 ohms |
| Dimensions (H x W x D): | 430 x 430 x 315 mm |

Contenuto della confezione:
