

## OMNITRONIC PAS-215PRO 2-Way Top

2-way speaker system for PA applications

Art.n.: 11039446

GTIN: 4026397438406



### Features :

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems

### Logistica

EAN / GTIN: 4026397438406

Peso : 23,00 kg

Lunghezza : 0.52 m

Larghezza : 0.45 m

Altezza : 0.77 m

### Dati tecnici :

Capacità di carico: Programma: 800W  
Nominale: 400W RMS

Intervallo di frequenza: 55 - 20000 Hz

Impedenza: 8 Ohm

Collegamenti:	Ingresso: Altoparlante via 2 x Presa da incasso per altoparlanti (F)
Altoparlante:	1 x 15" Woofer
Tipo di altoparlante:	Cassa compatta
Misure:	Larghezza: 43 cm Profondità: 36,5 cm Altezza: 70 cm
Peso:	21,05 kg
Components:	38 cm woofer (15"), 2.5 cm horn (1")
Connection:	2 Speaker sockets
Sensitivity:	97 dB
Maximum SPL:	124 dB
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°

---

**Contenuto della confezione:**

---