

PSSO K-215X 2-way top 600W
PRO PA speaker system

Art.n.: 11041110
GTIN: 4026397483048



L'articolo non è più disponibile.

Features :

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter
- Horn exit 35 mm (1.4")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- Driver di CELTO ACOUSTIQUE

Logistica

EAN / GTIN: 4026397483048
Peso : 35,00 kg
Lunghezza : 0.52 m
Larghezza : 0.48 m
Altezza : 0.79 m
Merci voluminose

Dati tecnici :

Capacità di carico:	Programma: 1200W
	Nominale: 600W RMS
Intervallo di frequenza:	44 - 19000 Hz
Impedenza:	8 Ohm

Collegamenti:	Ingresso: Altoparlante via 2 x Presa da incasso per altoparlanti (F)
Altoparlante:	1 x 15" Woofer
Tipo di altoparlante:	Cassa compatta
Uso del marchio:	Driver di CELTO ACOUSTIQUE
Misure:	Larghezza: 71 cm Profondità: 44,5 cm Altezza: 41,5 cm
Peso:	32,20 kg
Components:	38 cm woofer (15"), 3.6 cm horn (1.4")
Connection:	2 x Speakon
Sensitivity:	98 dB
Maximum SPL:	132 dB
Crossover frequency:	1.5 kHz
Dispersion angle:	80° x 50°
Dimensions (H x W x D):	710 x 445 x 415 mm