

OMNITRONIC MSM-110 S PRO Shotgun mic

Condenser microphone with ball joint

Art.n.: 13030836

GTIN: 4026397259124



Features :

- Designed for live sound reinforcement and broadcasting and in studio or live recording
- Set consisting of 360° rotatable and angular microphone head and powering module
- Narrow acceptance angle for long-distance sound pickup
- Excellent sound rejection from the sides and rear of mic
- Low inherent self-noise
- Operates on phantom power
- Incl. foam windscreen

Logistica

EAN / GTIN: 4026397259124

Peso : 0,33 kg

Lunghezza : 0.24 m

Larghezza : 0.11 m

Altezza : 0.06 m

Dati tecnici :

Tipo di capsula:	Condensatore
Intervallo di frequenza:	50 - 18000 Hz
Misure:	Lunghezza: 23,8 cm Diametro: Ø 19 cm
Peso:	0,13 kg
Type:	Condenser (back electret)
Operating principle:	Pressure gradient
Polar pattern:	Line + gradient
Sensitivity at 1 kHz:	10 mV/Pa; -36 dBu (±3 dB/Pa)
Nominal impedance:	250 ohms ±30%

Load impedance:	1250 ohms \pm 30%
Maximum SPL:	135 dB (THD <0.5% @ 1 kHz)
S/N ratio:	72 dB
Equivalent SPL:	21 dBA
Dynamic:	113 dB
Power supply:	16-52 V DC phantom power
Current consumption:	3.5 mA
Connection:	3-pin XLR
Dimensions (L x W x H):	19 x 19 x 238 mm

Contenuto della confezione:
