

OMNITRONIC MSM-111 S PRO shotgun mic

Condenser microphone with ball joint

Art.n.: 13030838

GTIN: 4026397259148



Features :

- Designed for live sound reinforcement and broadcasting and in studio or live recording
- Set consisting of a 360° rotatable microphone head and a powering module
- Narrow acceptance angle for long-distance sound pickup
- Excellent sound rejection from the sides and rear of mic
- Low inherent self-noise
- Operates on phantom power
- Incl. foam windscreen

Logistica

EAN / GTIN: 4026397259148

Peso : 0,33 kg

Lunghezza : 0.24 m

Larghezza : 0.11 m

Altezza : 0.05 m

Dati tecnici :

| | |
|--------------------------|-----------------------------------------|
| Tipo di capsula: | Condensatore |
| Intervallo di frequenza: | 50 - 18000 Hz |
| Misure: | Lunghezza: 23,8 cm Diametro: Ø 19 cm |
| Peso: | 0,13 kg |
| Type: | Condenser (back electret) |
| Operating principle: | Pressure gradient |
| Polar pattern: | Line + gradient |
| Sensitivity at 1 kHz: | 10 mV/Pa; -36 dBu (±3 dB/Pa) |
| Nominal impedance: | 250 ohms ±30% |

| | |
|-------------------------|----------------------------|
| Load impedance: | 1250 ohms \pm 30% |
| Maximum SPL: | 135 dB (THD <0.5% @ 1 kHz) |
| S/N ratio: | 72 dB |
| Equivalent SPL: | 21 dBA |
| Dynamic: | 113 dB |
| Power supply: | 16-52 V DC phantom power |
| Current consumption: | 3.5 mA |
| Connection: | 3-pin XLR |
| Dimensions (L x W x H): | 19 x 19 x 238 mm |

Contenuto della confezione:
