

## EUROLITE LED KLS-30 Compact Light Set

DMX LED spotlight set with 12 x 4in1 LED for mobile use

Art.n.: 42109603

GTIN: 4026397563641



**L'articolo non è più disponibile.**

### Features :

- Complete LED light set with four compact LED spots
- Crossbar with integrated DMX control unit
- Ultra-light ideally suited for mobile use
- Comes pre-assembled
- 3 QCL LEDs with 4 watts each per spot (RGBW)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 2, 3, 4, 6, 16, 20 or 24 DMX channels selectable
- Sound-control via built-in microphone, microphone sensitivity adjustable
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom fed socket for QuickDMX receiver (see accessories)
- DMX512 control via regular DMX controller
- Via DMX, each spot can be individually controlled
- Functions: RGBW color mixture, color presets, built-in programs, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a speaker stand (not included) or truss
- Black lacquered metal version with movable mounting bracket
- Ideal for bands, stages or solo entertainers
- Switch-mode power supply for operation between 100 and 240 volts
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; DMX; QuickDMX
- Già pre-programmato con Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Senza sfarfallio
- With a beam angle of 24°

### Logistica

EAN / GTIN: 4026397563641

Peso : 3,85 kg

Lunghezza : 0.50 m

Larghezza : 0.25 m

Altezza : 0.20 m

## Dati tecnici :

|                                                 |                                                                                   |
|-------------------------------------------------|-----------------------------------------------------------------------------------|
| Alimentazione elettrica:                        | 100-240 V AC, 50/60 Hz                                                            |
| Potenza totale installata:                      | 50 W                                                                              |
| Grado di protezione:                            | IP20                                                                              |
| Tipo di lampada:                                | Lampada a LED                                                                     |
| Raffreddamento:                                 | Raffreddamento a convezione passiva                                               |
| Attivazione:                                    | Stand-alone; DMX; QuickDMX                                                        |
| Pre-programmato con:                            | Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Proiezione:                                     | Senza sfarfallio                                                                  |
| Angolazione del fascio di luce:                 | 24°                                                                               |
| Angolazione del fascio di luce (1/2 picco):     | 24°                                                                               |
| Angolazione del fascio di luce (1/10 di picco): | 54°                                                                               |
| Colore della custodia:                          | Nero                                                                              |
| Misure:                                         | Larghezza: 45 cm<br>Profondità: 12 cm<br>Altezza: 18,5 cm                         |
| Peso:                                           | 3,10 kg                                                                           |
| DMX channels:                                   | 2/3/4/6/16/20/24                                                                  |
| DMX connection:                                 | 3-pin XLR                                                                         |
| QuickDMX connection:                            | 5-pin XLR                                                                         |
| Sound control:                                  | via built-in microphone                                                           |
| LED type:                                       | QCL 4 W                                                                           |
| Number of LEDs:                                 | 12                                                                                |
| Beam angle:                                     | 24°                                                                               |
| Dimensions (L x W x H):                         | 450 x 120 x 185 mm                                                                |
| Specifiche legali                               |                                                                                   |
| Prodotto speciale:                              | Non destinato all'illuminazione di ambienti domestici                             |
| Destinazione d'uso:                             | Illuminazione per effetti speciali                                                |