

## ANTARI DarkFX Spot 670

PRO DMX UV spot with 9 x 1.9 W UV LED, deep wavelength (365 nm)

Art.n.: 51100819

GTIN: 4719850658014



### Descrizione :

The Antari DarkFX Spot 670 is an efficient high-output and low-power consumption UV LED spot that delivers a peak wavelength of 365nm and radiant flux output of 6760 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.

Equipped with 9 x 1.9 W high-power UV LEDs, it features a 15° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED spot comes with an aluminium housing with an adjustable brackets for versatile mounting options.

The DarkFX Spot 670 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

### Features :

- High-efficiency UV LED
- Luce visibile minima
- Alte prestazioni a piena intensità
- Special optics will not degrade due to high UV exposure
- 9 LED 1,9 W high power ultravioletto (UV)
- Effetto UV
- Controllabile via stand-alone; DMX
- Senza sfarfallio
- With a beam angle of 15°
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

### Logistica

EAN / GTIN: 4719850658014

Peso : 3,45 kg

Lunghezza : 0.37 m

Larghezza : 0.23 m

Altezza : 0.19 m

## Dati tecnici :

|   |   |
|---|---|
| Alimentazione elettrica:                    | 100-240 V AC, 50/60 Hz  |
| Potenza totale installata:                  | 20 W  |
| Allacciamento elettrico:                    | Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Uscita di corrente:                         | 1 x PowerCON (grigio)   |
| Tipo di lampada:                            | Lampada a LED   |
| Tipo di LED:                                | 9 x 1,9 W high power ultravioletto (UV)   |
| Canali DMX:                                 | 1; 2  |
| Ingresso DMX:                               | 1 x Versione da incasso XLR (M) a 5 poli  |
| Uscita DMX:                                 | 1 x Versione da incasso XLR (F) a 5 poli  |
| Attivazione:                                | Stand-alone; DMX  |
| Proiezione:                                 | Senza sfarfallio  |
| Angolazione del fascio di luce (1/2 picco): | 15°   |
| Lunghezza d'onda:                           | 365 nm  |
| Colore della custodia:                      | Nero  |
| Materiale:                                  | Metallo   |
| Misure:                                     | Larghezza: 12,5 cm<br>Profondità: 20,5 cm<br>Altezza: 12,5 cm   |
| Peso:                                       | 2,86 kg   |
| Prodotto speciale:                          | Non destinato all'illuminazione di ambienti domestici   |
| Destinazione d'uso:                         | Illuminazione per effetti speciali  |

## Contenuto della confezione:

1 x Dispositivo  
1 x Cavo di rete/Cavo di alimentazione  
1 x Manuale d'uso