

EUROLITE TMH XB-230 Moving-Head Beam

High performance beam for 230 W discharge lamp

Art.n.: 51786820

GTIN: 4026397555974



L'articolo non è più disponibile.

Features :

- Very narrow beam angle with 3°
- With electronic ballast
- Color wheel with 14 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 7 Reflector 230 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Gobo
- Effetto Beam
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via DMX; stand-alone

Logistica

EAN / GTIN: 4026397555974

Peso : 21,60 kg

Lunghezza : 0.47 m

Larghezza : 0.43 m

Altezza : 0.62 m

- Già pre-programmato con LED PC-Control 512
- With a beam angle of 3°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	300 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a scarica
Attrezzature:	Gobo
Raffreddamento:	Ventola
Attivazione:	DMX; stand-alone
Pre-programmato con:	LED PC-Control 512
Angolazione del fascio di luce:	3°
Angolazione del fascio di luce (1/2 picco):	3°
Colore della custodia:	Nero
Misure:	Larghezza: 39,5 cm Profondità: 32 cm Altezza: 51 cm
Peso:	19,14 kg
DMX channels:	16
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	18 Hz
Color-wheel:	14 dichroic filters plus open
Static gobo-wheel:	17 gobos and open
Maximum PAN-movement:	540°
Maximum TILT-movement:	250°
Beam angle:	3°
Dimensions (L x W x H):	395 x 320 x 510 mm
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali