

REUTLINGER Cable Glider Type 50SVIII-GK14/28W bk

Cable glider, up to 90 kg work load

Art.n.: 58010551

GTIN: 4026397595963



Descrizione :

Certified cable holder

Cable holders can be used for easily suspending static workloads on attachment ropes. No tools are required. The load can be hung at any position and height and easily be re-positioned.

The REUTLINGER cable holders are the only system certified by two independent certification bodies. This cable holder boasts of a TÜV certificate and a German BGV C1 certificate and can be used in entertainment technology.

TÜV GS and BGV C1 - double-tested and double-certified

REUTLINGER® grippers type 50 SV III, type 66 SV III and type 80 SV III are not only certified as safe (GS) by the German TÜV, they have also been licensed for use within the scope of standard DGUV Regulation 17 (BGV C1).

The DGUV Test certificate authorises these grippers for use within the scope of the accident prevention regulations issued by the German employers' liability insurance associations in respect of staging and production facilities.

The test seal of the DGUV is conferred only after extensive examining of all load applications.

Further testing simulated most anticipated mis-applications.

REUTLINGER® gripper ranges 50, 66 and 80 are the only load-bearing devices certified by the DGUV for use in mobile production facilities.

Features :

- Per il diametro della fune da 4,0 a 5,0 mm
- Meccanismo a 6 sfere
- With fork 14 x 28 black zinc plated
- Nota: i supporti per funi metalliche non devono essere utilizzati in modo dinamico e devono essere utilizzati almeno in coppia.

Logistica

EAN / GTIN: 4026397595963

Peso : 0,37 kg

Lunghezza : 0.17 m

Larghezza : 0.12 m

Altezza : 0.03 m

- Filettatura M12
- Made in Germany
- Certificato BG
- Certificato TÜV/GS
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Per il diametro della fune:	4 mm - 5 mm
Carico di lavoro:	5 mm: 90 kg 4 mm: 60 kg
Colore:	Nero
Filettatura:	Filettatura M12 x 17 mm
Apertura:	14-28 mm
Misure:	Lunghezza: 12,20 cm Diametro: Ø 2,50 cm
Peso:	0,37 kg

Contenuto della confezione:
