

REUTLINGER Cable glider type 50SVII-RM12 bk

Cable glider, up to 130 kg work load

Art.n.: 58010574

GTIN: 4026397400403



L'articolo non è più disponibile.

Descrizione :

Certified cable holder

Cable holders can be used for easily suspending static workloads on attachment ropes. No tools are required. The load can be hung at any position and height and easily be re-positioned.

The REUTLINGER cable holders are the only system certified by two independant certification bodies. This cable holder boasts of a TÜV certificate and a German BGV C1 certificate and can be used in entertainment technology.

TÜV GS and BGV C1 - double-tested and double-certified

REUTLINGER® grippers type 50 SV II, type 66 and type 80 SV II are not only certified as safe (GS) by the German TÜV, they have also been licensed for use within the scope of standard DGUV Regulation 17 (BGV C1).

The DGUV Test certificate authorises these grippers for use within the scope of the accident prevention regulations issued by the German employers' liability insurance associations in respect of staging and production facilities.

The test seal of the DGUV is conferred only after extensive examining of all load applications.

Further testing simulated most anticipated mis-applications.

REUTLINGER® gripper ranges 50, 66 and 80 are the only load-bearing devices certified by the DGUV for use in mobile production facilities.

Features :

- For rope diameters 4.0 to 5.0 mm
- 6-ball mechanism
- With eyering DIN 582 M12 black zinc plated C15E
- TÜV-GS
- German BG certificate

Logistica

EAN / GTIN: 4026397400403

Peso : 0,26 kg

Lunghezza : 0.12 m

Larghezza : 0.03 m

Altezza : 0.06 m

- Please note: Cable gliders must not be used for dynamic loads. Always use at least 2 cable gliders for every suspended object.
- Filettatura M12
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Carico di lavoro:	5 mm: 130 kg 4 mm: 80 kg
Diametro anello:	Esterno: 54 mm Interno: 30 mm
Filettatura:	Filettatura M12 x 17 mm
Misure:	Lunghezza: 10,60 cm
Peso:	0,26 kg
Diameter:	25 mm
Thread:	M12
Thread length:	17 mm
Ring outer diameter:	54 mm
Ring inner diameter:	30 mm