



Descrizione :

In fields of advertising and information, electronic signs and moving messages respectively, become more and more popular. And this is not next door to a miracle if you look at the spectrum of possibilities. The different units of the ESN-series are not only able to show 93 standard characters in 14 fonts, to attract attention, the moving messages are also equipped with various display effects. These effects are performed in six diverse speeds. Furthermore, with the option to get signs programmed via a network, the series offers a real handy advantage.

Features :

- Large-scale information board for indoors and protected areas
- Ideal for welcome, announcements, special events, orientation etc.
- With 5-mm-LEDs for ideal readability from up to 25 meters distance
- Color and background color freely selectable via red/green/yellow LEDs
- High resolution with 54 mm character height per display line
- Single-line display with up to 13 visible characters
- 93 standard characters (letters/numbers) capitalized/small letters, symbols and language specific characters
- 14 fonts, 13 more fonts can be imported
- Fonts-manager for selecting different fonts, font sizes, letter cutting (bold) and for completely redesigning fonts
- Flash adjustable for emphasizing the message
- 50 different display effects (e.g. scroll up) freely selectable for In Mode and Out Mode
- 6 different speeds adjustable
- Display time of the message adjustable between 0 and 60 seconds
- Playlists of individual messages programmable

Logistica

EAN / GTIN: 4026397271621

Peso : 2,85 kg

Lunghezza : 0.81 m

Larghezza : 0.11 m

Altezza : 0.16 m

- With Timer-function (operation intervals and ignore times freely programmable)
- Permanent Flash-memory with 1 GB capacity
- Easy installation and comfortable operation via remote control (optional)
- Installation clamps and wall mounting included in the delivery
- Software-CD included in the delivery for comfortable programming
- Time display in different formats (24 h, 12 h AM/PM, seconds, time zone)
- Date in different styles (DD.MM.YYYY, US/UK or MM.DD.YYYY)
- Selection of year, month or day of the week in letters or numbers
- Freely programmable graphic-patterns via Picture Manager
- Net Manager for operating several Moving Messages
- Interfaces via RS232 (serial) or Ethernet (TCP/IP-protocol)
- RS232-connection via RJ11 plug and 9-pin SUB-D socket
- 10 m data-cable for RS232-connection included in the delivery
- RS232-connection extendable to max. 20 m (optional)
- IP-address for Ethernet-control freely programmable
- Minimum system-requirements: CPU 500 MHz or higher, VGA-card with small font, 128 MB memory, 10 MB of free hard disc space, CD-Rom drive, free COM-port or Ethernet-port, Windows 9X or higher, mouse, monitor refresh rate 60 Hz or higher
- 560 LED 5 mm R/G/Y
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via Cavi di rete; Telecomando IR (non in dotazione)

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Potenza totale installata:	15,00 W
Classe di protezione:	CL III
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore cavo (M) versione da incasso cavo di alimentazione con spina europea (in dotazione)
Lunghezza cavo:	Massimo 20 m
Pila:	2 x 1.5 V AA Mignon LR06 alkaline manganese presente
Tipo di LED:	560 x 5 mm R/G/Y
Connessione di rete:	Protocol: Ethernet TCP/IP via 1x RJ-45 (F) versione da incasso
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Cavi di rete; Telecomando IR (non in dotazione)
Immagine:	Massimo 7x80 px
Rappresentazione:	1 linee, 13 visible characters 8 colors 4 background colors
Testo:	93 with 2000 segno 14 fonts 120 symbols
Colore della custodia:	Nero
Collegamenti:	RS 232 via RJ11 (F) versione da incasso RS 485 via RJ11 (F) versione da incasso
Schermo:	61 cm x 5,5 cm
Misure:	Larghezza: 66 cm Profondità: 5 cm Altezza: 10,2 cm
Peso:	2,50 kg

Prodotto speciale: Non destinato all'illuminazione di ambienti
domestici

Destinazione d'uso: Illuminazione per effetti speciali

Contenuto della confezione:

1 x Dispositivo
1 x CD
1 x alimentatore esterno
1 x Cavo di rete/Cavo di alimentazione
1 x Cavi di rete
1 x cavi adattatori
2 x materiale di fissaggio
2 x angolo
4 x viti
1 x Manuale d'uso