

OMNITRONIC WMS-5S PA Wall Speaker

Altoparlante a 2 vie con supporto, ELA tecnica 100 V, 40 W RMS

Art.n.: 80710536

GTIN: 4026397523096



Features :

- 100 V technology with high-quality components for hifi sound
- 2-way bass-reflex system with 13 cm bass-midrange speaker (5") and 2.5 cm tweeter (1")
- Suitable for 100 V or 8-ohm operation
- 4-step power selector
- Weather-proof plastic cabinet (IP44) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket
- Loose cable ends
- For outdoor and indoor amplifying systems

Logistica

EAN / GTIN: 4026397523096

Peso : 4,25 kg

Lunghezza : 0.34 m

Larghezza : 0.24 m

Altezza : 0.19 m

Dati tecnici :

Grado di protezione:	IP44
Capacità di carico:	Programma: 80W Nominale: 40W RMS (8 Ohm) Nominale: 40W RMS (100 V ELA)
Intervallo di frequenza:	70 - 20000 Hz
Sensibilità:	90 dB
Impedenza:	ELA tecnica 100 V; 8 Ohm
Alimentazione di derivazione:	5W; 10W; 20W; 40W RMS via selettore switchable

Altoparlante:	1 x 5" Woofer 1" tweeter
Tipo di altoparlante:	Cassa compatta
Misure:	Larghezza: 19,6 cm Profondità: 15,7 cm Altezza: 29,5 cm
Peso:	3,70 kg

Contenuto della confezione:
